

VARILLA CORRUGADA



VARILLA CORRUGADA: FICHA TÉCNICA

| Varilla No. | Medida | | Peso kg/m | Perímetro mm | Área cm | Piezas ton. |
|-------------|--------|-------|-----------|--------------|---------|-------------|
| | mm | pulg. | | | | |
| 2.5 | 7.9 | 5/16 | 0.384 | 24.8 | 0.49 | 217 +- 7 |
| 3 | 9.5 | 3/8 | 0.557 | 29.8 | 0.71 | 149 +- 4 |
| 4 | 12.7 | 1/2 | 0.996 | 39.9 | 1.27 | 84 +- 2 |
| 5 | 15.9 | 5/8 | 1.560 | 50.0 | 1.99 | 54 +- 1 |
| 6 | 19.1 | 3/4 | 2.250 | 60.0 | 2.87 | 37 +- 1 |
| 8 | 25.4 | 1 | 3.975 | 79.8 | 5.07 | 21 |
| 10 | 31.8 | 1 1/4 | 6.225 | 99.9 | 7.94 | 13 |
| 10 | 38.1 | 1 1/2 | 8.938 | 119.7 | 11.40 | 9 |

Longitud a 9.15 y 12.20 mts.

NORMA DE FABRICACIÓN NMX-B-506 CANACERO

Para comprar este producto llama al
(55) 55 32 32 03

ventas@ferrex.com.mx

www.materialesparaconstruccion.com.mx

